


Miniature Circuit Breaker MCB6/1-3Pole





All dimensions in millimetres











Technical Specifications

Rated Current	1, 2, 3 pole 1, 2, 3, 4, 6, 10, 16, 20, 25, 32, 40, 50, 63A
Rated Voltage(Un)	1pole AC230(240)V 2pole AC400(415)V 3pole AC400(415)
Rated frequency	1, 2, 3 pole 50(60)Hz
Curve Magnetic releases operate	1, 2, 3 pole B , C , D
Short-circuit breaking capacity(Icn)	1, 2, 3 pole 6000A
Dimensions	1pole 72mm(L) 80mm(H) 18mm(W) 2pole 72mm(L) 80mm(H) 36mr 3pole 72mm(L) 80mm(H) 54mm(W)
Magnetic releases operate	1pole B curve:between 3 and 5ln 2pole C curve:between 5 and 10l 3pole D curve:between 10 and 14ln
Endurance	1, 2, 3 pole ≥4000
Terminal protection	1, 2, 3 pole lp20
Installation method	1, 2, 3 pole DIN rail
Operating temperature	1, 2, 3 pole $-5^{\circ}\text{C} \sim +40^{\circ}\text{C}$
Standards	1, 2, 3 pole IEC60898
Approval number	1, 2, 3 pole N17682
ACMA approval	1, 2, 3 pole N11193
RCM approval	1, 2, 3 pole N5400

www.pulset.com

PULSET Pty Ltd ABN. 33 095 649 228 All Correspondence: P.O Box 6644, Wetherill Park BC NSW 2164 1300 Pulset (785738) P. +61 2 9756 5000 F. +61 2 9756 6192 E. mail@pulset.com W. www.pulset.com

SYDNEY MELBOURNE ADELAIDE BRISBANE PERTH HOBART 02 9756 5000 03 9095 7333 08 7221 2999 07 3166 8222 08 6467 7755 03 6281 2422



1/2

