


All Dimensions in millimetres

CE CB AS/NZS



Technical Specifications

Maximum	80A
Rated Voltage(Un)	AC 240V(415V)
Rated frequency	50(60)Hz
Phase	Three Phase
Starting Current	0.4%Ib
Insulation Performance	AC voltage withstand 2kV for 1 minute; Impulse voltage withstand 6kV -- 1.2/50µs waveform
Accuracy Class	Class 1.0
Dimensions	125mm(L) 88mm(H) 73mm(W)
Installation method	DIN rail
Humidity	Less than 75%
Operating temperature	-25°C ~ +55°C
Storage temperature	-30°C ~ +65°C
Display	Analog
Standards	IEC61063



KWH/3

www.pulset.com

PULSET Pty Ltd ABN. 33 095 649 228 All Correspondence: P.O Box 6644, Wetherill Park BC NSW 2164
1300 Pulset (785738) P. +61 2 9756 5000 F. +61 2 9756 6192 E. mail@pulset.com W. www.pulset.com

SYDNEY MELBOURNE ADELAIDE BRISBANE PERTH HOBART
02 9756 5000 03 9095 7333 08 7221 2999 07 3166 8222 08 6467 7755 03 6281 2422

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Pulset nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.